

# 1200D

## Double Magnetic Lock



Built to provide 1200 lbs of holding force, per door, for double door configurations, this easy to install magnetic lock includes LED status indicator, bond sensor and door status sensor to signal a powered and securely locked door. Ideal for interior or exterior applications.

## Features

### Standard Features

- Built-in arc suppression
- Instant release, no hysteresis
- Self-drilling TEC screws
- Non-aluminum parts are plated to resist corrosion
- E-Z mount header bracket and template provided for easy installation, no special tools required
- Can be used with any access control system
- Bond sensor and door status sensors plus bi-color LEDs signal a powered and securely locked door
- Clear anodized (US28) finish standard
- Limited lifetime warranty

### Options

- **DURO** Duranodic finish (US 40) available, add DURO to end of standard part number when ordering.
- Dress covers in polished chrome and brass are available. See "Magnetic Lock Accessories" for options.

## Specifications

### Certifications & Listings

- UL 294 listed
- UL 10C fire rated
- CAN/ULC-S104 fire door conformant
- ULC-S527 listed
- UL 864 listed

### Holding Force

- 1200 lbs, per magnet

### Dimensions

- Magnet size: 21" L x 2-7/8" H x 1-1/2" W
- Armature size: 7-1/2" L x 2-3/8" H x 5/8" W

### Electrical

- 12 or 24 VDC, field selectable
- Current draw, per magnet: 505 mA at 12 VDC, 260 mA at 24 VDC
- Bond sensor has SPDT 3A relay contacts, per magnet

### Operating Temperature

- +14 to +131F [-10 to +55C]