

GT-DMB-N

Video Entrance Station

The GT-DMB-N video entrance station has a PTZ camera, LCD screen, motion sensor, keypad, and buttons to search and select menu options.

The keypad is used for direct dialing and tenant entry access. Its LCD screen can display a greeting message, the tenant directory, and system status. If the GT-DMB-N is set to energy saver mode, the screen is activated by the motion sensor. A built-in user guide can be displayed in one of six languages. This guide provides operational assistance with visual icons and the option for audible instruction.

The GT-DMB-N works on a common bus wiring; call and communications are carried on 2-conductor wire and the video signal is carried on a second 2-conductor wire. A separate power supply provides voltage for the LCD screen, while the power for the audio and video is supplied on the common bus wires.



- **PTZ camera with 170° angle view**
- **Hands-free communication**
- **Direct dialing, alphabetical scrolling, or “jump” scrolling by letter to select tenant**
- **Digital panel stores up to 500 tenant names/number locations and 500 unique access codes to activate door release**
- **Voice annunciation in English, French, German, Spanish, Dutch, and Italian**
- **Alpha-numeric room numbers and/or names can be programmed with software**
- **Scrolling welcome message, up to 160 characters, adjustable scroll speed**
- **Weather and vandal resistant**
- **Tenant directory programming with NFC technology**
- **PC configuration via USB**
- **Mobile app configuration via NFC (Android™ only, requires Aiphone GT Setup Tool app)**
- **Motion activated 3-1/2" LCD screen can display a customized greeting, operation instructions, or standby image**

- Power Source** 24V DC—use specified number of PS-2420ULs per system configuration
- Communication** Hands-free (VOX)
- Camera** Type: 1/4" CMOS
View Area: 100° vertical x 170° horizontal
- Video Display** 3.5" LCD screen
- Door Release** Form C dry contact, 24V AC/DC, 4A
- Operating Temp** -22°~140°F (-30°~60°C)
- Material** Stainless steel
- Mounting** Flush mount with GF-3B or surface mount with SBX-GTDMB (both sold separately)
- Wire Type** 2-cond., solid, non-shielded, PE insulation—use Aiphone #872002 for audio and #871802 for video and power
- Weight** ≈ 2.64lbs (1.2 kg)
- Dimensions** 12 5/8H 5 7/8"W